



Huawei eSpace 7903X Expansion Module



Figure 1-1 eSpace 7903X expansion module



Figure 1-2 eSpace 7903X expansion module used with eSpace 7950

**Used with eSpace 7950
Provides a rich set of functions including speed dial, phone lock, and phone sleep, which is applicable to users who need to manage, and learn about various call states.**

- 5-inch color Liquid Crystal Display (LCD) screen, 800 x 480 high-resolution
- 20 programmable buttons with dual-color LEDs, and 2 page buttons with monochrome LEDs
- A second page button that provides access to additional 20 programmable buttons (for a total of 40 buttons)
- Icons displayed for phone lock and sleep functions
- Dual-color LED indicators to tell different line states of contacts
- A rich set of functions, such as speed dial, phone lock, and phone sleep
- Table1 Multi-language support

eSpace 7903X is a multi-functional IP phone expansion module, which is ideal for managers, secretaries, and receptionists at the front desk. eSpace 7903X is used with eSpace 7950 to provide various functions including speed dial, phone lock, and phone sleep. With a single eSpace 7903X, eSpace 7950 increases the number of programmable buttons to 40 and provides optimized viewing through the 5-inch color LCD screen. eSpace 7903X helps users use eSpace 7950 more efficiently with better user experience.

Table1 eSpace 7903X Functions, Features and Technical Specifications

Category	Parameter	Specification
IP phone support	eSpace 7950	
Screen	5-inch, 800 x 480 pixel, color LCD screen	
Language display	Arabic, Chinese (simplified and traditional), English, French, Portuguese, and Spanish	
Buttons	20 programmable buttons and 2 page buttons	
Maximum number of pages	2 pages	
Maximum number of programmable buttons	40	
Number of expansion modules that can be used	<ul style="list-style-type: none"> Powered by eSpace 7950: only 1 expansion module Table1 Powered by external power supply: up to 3 expansion modules 	
Functions	Busy Lamp Field (BLF), contact group, speed dial, XML application, phone lock, and sleep	
Electrical features	Power adapter	Input: 100–240 V AC Output: 5 V DC, 2 A Support for China, Europe, America, Britain, and Australia standards
	Power consumption	3 W
Environmental requirements	Operating temperature	0° C to 45° C
	Operating humidity	10% to 95%
	Storage temperature	–25° C to +70° C
	Storage humidity	10% to 95%
Physical features	Dimensions	209 mm x 130 mm x 67.5 mm
	Weight	0.41 kg
	Installation mode	Desktop installation